
GU112X16G-7000BL

SIMPLIFIED DATASHEET

■ Features

Power-saving model of GU112X16G-7000B.

■ Physical dimension



Specifications

■ Electrical Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Power supply voltage	VCC	4.75	5.00	5.25	VDC	–

■ Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
'L' Logic Input Current						
D0-D7,/WR,/RD	IIL1	–	–	-0.15	mA	VIN=0V
/RESET	IIL2	–	–	-0.6	mA	VIN=0V
'H' Logic Input Current						
D0-D7,/WR,/RD,/RESET	IIH	–	–	1.0	μADC	VIN=5V
Logic Input Voltage	VIH	0.8VCC	–	VCC	VDC	–
D0-D7,/WR,/RD,/RESET	VIL	0	–	0.2VCC	VDC	–
Logic Output Voltage	VOH	3.8	–	VCC	VDC	IOH=-1.5mA
D7(Busy flag), PBUSY	VOL	0	–	0.6	VDC	IOL=1.6mA
Logic input resistance						
SIN	RIN	3	–	–	KΩ	–
Logic Input Voltage	VIH	3.0	–	+15	VDC	–
SIN	VIL	-15	–	0.5	VDC	–
Logic Output Voltage	VOH	4.0	–	VCC	VDC	RL=3KΩ
SBUSY	VOL	0	–	0.5	VDC	RL=3KΩ
Power Supply Current 1	ICC-1	–	175	220	mADC	All dots ON
Power Supply Current 2	ICC-2	–	110	140	mADC	All dots OFF
Power Supply Current 3	ICC-3	–	11	15	mADC	Display power OFF
Power Consumption		–	0.9	1.15	W	All dots ON

■ Optical Specifications

Parameter	
Luminance	350 cd/m^2 Min. (700 cd/m^2 Typ.)
Color of illumination	Green (Blue-Green)

■ Environmental Specifications

Parameter	
Operating Temperature	-40 ~ +85 degrees celsius
Storage Temperature	-60 ~ +85 degrees (Under 168 hours)/-40 ~ +85 degrees (Or more)
Operating Humidity	20 ~ 80% R.H. (non-condensing)
Storage Humidity	20 ~ 80% R.H. (non-condensing)
Vibration (non-operating)	10-55-10Hz, all amplitude 1mm, 30 minutes, X-Y-Z
Shock (non-operating)	392m/s2 (40G) 9ms X-Y-Z, 3 times each direction

■ Physical Specifications

Parameter	
Number of Dots	1,792 (112 x 16)
Display Area	52.50 mm x 11.45 mm
Dot Size (X x Y)	0.330 mm x 0.575 mm
Dot Pitch (X x Y)	0.470 mm x 0.725 mm
Weight	About 31 g

■ Interface

Parallel(CMOS), Asynchronous Serial (RS232)

■ Pin Assignment (Parallel)

Pin No.	Signal	Pin No.	Signal
1	GND	8	D1
2	VCC	9	D2
3	NC	10	D3
4	RS	11	D4
5	/WR	12	D5
6	/RD	13	D6
7	D0	14	D7(PBUSY)

(Asynchronous Serial)

Pin No.	Signal
1	VCC
2	SIN
3	GND
4	SBUSY
5	NC
6	/RESET

Baud Rate Setting
9600bps
19200bps
38400bps*
115200bps
(*:Default setting)

■Selectable Font

Parameter		*ANK(Alphabet, Numeric, Kana)
Character font type	5 x 7	ANK, International
Character width	Fixed/Proportional character format 1&2	
Character numbers	16 x 2 by 5 x 7 dot ASCII	
	18 x 2 by 5 x 7 dot Proportional	

■ Functions

Parameter
Control command
Scroll display action
Proportional Font function
User-Windows function
AND/OR/XOR Mixture display
Reverse display
Dot unit real-time bit image display
Download character function
Font Magnification function
etc.

RoHS COMPLIANT

Leaflet contents, and specifications and external appearance of products, may change without notice.
Please confirm product details in the specification.

(C)Copyright NORITAKE ITRON CORP.

'15/10